

{Never write scripts again}

Python CLI applications & TDD



Swiss Python Summit 2022

{ Peter Bittner }

Developer
of people, companies and code

@peterbittner, django@bittner.it



cli-test-helpers PythonTurtle ansible-role-software
behave-django django-analytical .djangocms-maps django-probes
django-bootstrap-static django-apptemplates django-organice pyclean

Automated tests are important
but ...

... in my case ...
they don't make all that sense.

I need to move fast!





*“The only way to go fast
is to go well.”*

--- Robert C. Martin



Source: Technology and Friends, Episode 354, 2015

CLI Applications & TDD

1. What's wrong with scripts?
2. *Coding example #1* (refactoring)
3. Why CLI applications?
4. Challenges with writing tests
5. *Coding example #2* (cli & tests)



```
1 from application import cli
2 from cli_test_helpers import shell
3
4 def test_cli_entrypoint():
5     result = shell("python-summit --help")
6     assert result.exit_code == 0
```

What's Wrong with Scripts?



```
1 print("This is important code")
2
3 for index, arg in enumerate(sys.argv):
4     print(f"[{index}]: {arg}")
```

- Easy to get started
- Limited possibilities for structure
- Hard to (unit) test
- No dependency management
- Deployment may require care
- Custom user experience

Coding Example #1

```
● ● ●  
$ cowsay -e ~~ WHAT IS WRONG WITH SCRIPTS? | lolcat
```

```
< WHAT IS WRONG WITH SCRIPTS? >
```

```
-----  
 \      ^  ^  
  \      --  
   (~~) \_____  
  (  ) \      ) \ / \  
      | | -----w |  
      | |           | |
```

Refactor a script

Why CLI Applications?



```
1 def main():
2     print("Usage: foo <bar> --baz")
3
4 if __name__ == "__main__":
5     main()
```

- Standardized user experience
- More possibilities for structure
- Possibilities for all kinds of testing
- Dependency management
- Packaging & distribution

Argparse



```
1 import argparse
2 from . import __version__
3
4 def parse_arguments():
5     parser = argparse.ArgumentParser(description=__doc__)
6     parser.add_argument('--version', action='version',
7                           version=__version__)
8     parser.add_argument('filename')
9     args = parser.parse_args()
10    return args
11
12 def main():
13     args = parse_arguments()
14     ...
```

Click



```
1 import click
2
3 @click.command()
4 @click.version_option()
5 @click.argument('infile', type=click.File(exists=True))
6 def main(infile):
7     click.echo(infile.read())
```

Docopt



```
1  """Foobar
2  Usage:
3    foobar (-h | --help | --version)
4    foobar [-s | --silent] <file>
5    foobar [-v | --verbose] <file>
6  Positional arguments:
7    file          target file path name
8  Optional arguments:
9    -h, --help      show this help message and exit
10   -s, --silent     don't show progress output
11   -v, --verbose    explain progress verbosely
12   --version        show program's version number and exit
13  """
14  from docopt import docopt
15  from . import __version__
16
17  def parse_arguments():
18      args = docopt(__doc__, version=__version__)
19
20      return dict(
21          file=args['<file>'],
22          silent=args['-s'] or args['--silent'],
23          verbose=args['-v'] or args['--verbose'],
24      )
```

Challenges with Writing Tests



```
1 def test_cli():
2     with pytest.raises(SystemExit):
3         foobar.cli.main()
4         pytest.fail("CLI doesn't abort")
```

- How test our CLI configuration?
- Control taken away from us
- Package features require deployment

CLI Test Strategy

```
1 def a_functional_test():
2     result = shell('foobar')
3     assert result.exit_code != 0, result.stdout
4
5 def a_unit_test():
6     with ArgvContext('foobar', 'myfile', '--verbose'):
7         args = foobar.cli.parse_arguments()
8         assert args['verbose'] == True
```

1. Start from the user interface with **functional tests**.
2. Work down **towards unit tests**.

Functional Tests (User Interface)



```
1 def test_entrypoint():
2     """Is entrypoint script installed? (setup.py)"""
3     result = shell('foobar --help')
4     assert result.exit_code == 0
```

Drive the code from "outside"

"Is the **entrypoint** script installed?"

"Can package be run as a Python **module**?"

"Is **positional** argument *<foo>* available?"

"Is **optional** argument *--bar* available?"

Unit Tests



```
1 import foobar
2 from cli_test_helpers import ArgvContext
3 from unittest.mock import patch
4
5 @patch('foobar.command.process')
6 def test_process_is_called(mock_command):
7     with ArgvContext('foobar', 'myfile', '-v'):
8         foobar.cli.main()
9
10     assert mock_command.called
11     assert mock_command.call_args.kwargs == dict(
12         file='myfile', silent=False, verbose=True)
```

Stay in the Python code

Tox

Installs your CLI before
running the test suite!

```
1 [tox]
2 envlist = py{38,39,310}
3
4 [testenv]
5 description = Unit tests
6 deps =
7     cli-test-helpers
8     coverage[toml]
9     pytest
10 commands =
11     coverage run -m pytest {posargs}
12     coverage xml
13     coverage report
```

Coding Example #2

```
● ● ●  
$ cowsay MOO! I ♥ CLI-TEST-HELPERS | lolcat
```

```
< MOO! I ♥ CLI-TEST-HELPERS >
```

```
-----  
 \      ^  ^  
  \      --  
   (oo) \  
  (__) \      ) \/\   
        ||----w |  
        ||      ||
```

Write and run tests with
`cli-test-helpers`

Thank you!
for your precious time



Painless Software
Less pain, more fun.

